

## TRI-BUILT<sup>®</sup> Modified App Smooth

### SECTION 1: PRODUCT & COMPANY IDENTIFICATION

PRODUCT NAME:	TRI-BUILT <sup>®</sup> APP Smooth	Distributed By:	TRI-BUILT <sup>®</sup> Materials Group
CHEMICAL NAME:	Mixture		
MANUFACTURER:	Polyglass USA, Inc.	ADDRESS:	15 East Union Ave., East Rutherford, NJ 07073
ADDRESS:	1111 West Newport Center Drive, Deerfield Beach, FL 33442	PHONE:	1-800-516-1485
PHONE:	(888) 410-1375	INTERNET:	www.tribuiltmaterialsgroup.com
EMERGENCY PHONE:	800-424-9300 Chemtrec		
EFFECTIVE DATE:	8/7/2014		
Signature of Preparer:	W. Rammacher / Allied Building Products Corp.		

### SECTION 2 - PRODUCT INGREDIENT

INGREDIENT NAME	COMMON NAME	CAS number	% Weight	Exposure Limit (OSHA)	Exposure Limit (ACGIH)
Petroleum Asphalt	Asphalt	8052 42 4	53.5 - 61.0	5 mg/m <sup>3</sup> PEL	
Calcium Carbonate	Limestone	1317 65 3	7.1 - 20.3	5 mg/m <sup>3</sup> PEL (Respirable) 15 mg/m <sup>3</sup> PEL (Total)	
Polyethylene	Polyethylene	9002 88 4	0 - 2.6	5 mg/m <sup>3</sup> PEL (Respirable) 15 mg/m <sup>3</sup> PEL (Total)	
Polypropylene	Polypropylene	9003 07 0	4.5 - 7.9	Not Established	
Ethylene Propylene Copolymer	Copolymer	9010 79 1	5.6 - 22.4	5 mg/m <sup>3</sup> PEL (Respirable) 15 mg/m <sup>3</sup> PEL (Total)	
Non-woven Polyester	Polyester mat	None assigned	2.8 - 3.7	Not established	
Cont Filament glass fiber	Fiberglass mat	65997 17 3	0 - 1.8	5 mg/m <sup>3</sup> PEL (Respirable) 15 mg/m <sup>3</sup> PEL (Total)	1 fiber/cc TLV 5 mg/m <sup>3</sup> TLV (Total)
Crystalline silica, Quartz	Sand	14808 60 7	5.3 - 6.9	0.1 mg/m <sup>3</sup> PEL (Respirable)	

### SECTION 3 - PHYSICAL/CHEMICAL DATA

PROPERTIES	UNIT	DATA
Appearance	N/A	Black roll
Boiling point	deg F	>650
Evaporation Rate	N/A	N/A
Flash Point	deg F	>430
Melting Point	deg F	>290
Odor	N/A	Mild asphalt/petroleum odor
Ph (undiluted product)	N/A	N/A
Saturation in air	%	N/A
Solids Content	N/A	N/A
Specific gravity	g/cc	1.02 - 1.30
Vapor Density	Air = 1	N/A
Vapor Pressure	N/A	N/A
Viscosity	cP	N/A
VOC	g/liter	N/A
Volatility	%	< 0.1
Water solubility	%	< 0.1

## SECTION 4 - FIRE AND EXPLOSION DATA

FLAMMABILITY PROPERTIES	
Flash point	>430 deg F (ASTM D92)
Lower Explosive	Limit Undetermined
Upper Explosive	Limit Undetermined
RECOMMENDED EXTINGUISHING MEDIA	
Dry chemical, foam, water fog, CO2	
UNUSUAL FIRE OR EXPLOSION HAZARDS	
Burning will produce black smoke	
SPECIAL FIRE FIGHTING PROCEDURES	
Wear self contained breathing apparatus	

## SECTION 5 - HAZARD IDENTIFICATION

ACUTE HEALTH EFFECTS	
Irritation of eye, nose, throat, and skin	
CHRONIC HEALTH EFFECTS	
Insufficient evidence of cancer induced by exposure to asphalt fumes. The International Agency for Research on Cancer (IARC) considered Crystalline Silica as a human carcinogen. Prolonged exposure to Crystalline Silica containing dust can lead to Silicosis. Continuous filament glass fibers are not classified as Carcinogens. However no significant health hazards are likely to occur due to the product form and nature of use.	
Upper respiratory system	
MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED	
Pre-existing respiratory conditions	
SIGNS/SYMPTOMS OF OVEREXPOSURE	
Inhalation	Headache, nausea, coughing, irritation of the upper respiratory system
Skin Contact	Burns caused by contact with hot material
Skin absorption	Not applicable
Ingestion	Not intended to be ingested
Eye Contact	Irritation/redness may occur

## SECTION 6 - FIRST AID PROCEDURES

INHALATION	
Remove affected person to fresh air	
SKIN CONTACT	
Rinse with cool water	
SKIN ABSORPTION	
Not applicable	
INGESTION	
Do not induce vomiting. Treat symptomatically.	
EYE CONTACT	
Flush with copious quantities of water. Consult a physician if irritation persists.	

## SECTION 7 - STABILITY/REACTIVITY DATA

SUMMARY	
Material is stable. Hazardous polymerization will not occur.	
CHEMICAL INCOMPATIBILITIES	
Strong oxidizing agents, strong acids and alkalines.	
CONDITION TO AVOID	
Strong oxidizing agents at elevated temperatures and uncontrolled fumes.	
THERMAL STABILITY	
Stable	

## SECTION 8 - HANDLING, USE AND DISPOSAL

### PROCEDURES FOR SPILLS/LEAKS

Not applicable

### WASTE DISPOSAL METHOD

Standard refuse disposal. Wastes are classified as non-hazardous by U. S. Environmental Protection Agency (EPA) and as per definition by Resource Conservation and Recovery Act (RCRA). Follow all local, state, and federal regulations governing waste disposal.

Use protective equipment as described in Section IX. Keep away from heat or flame and protect from the elements.

### HYGIENIC PRACTICE

Wash after any skin contact.

## SECTION 9 - EXPOSURE CONTROL/PERSONAL PROTECTION

### EYE

Wear safety glasses with side shields.

### SKIN

Wear leather or cotton gloves (impervious)

### VENTILATION

Although normal conditions of product use does not warrant any special ventilation, use in well ventilated area.

### RESPIRATORY

None required unless used with hot asphalt. Use breathing apparatus (only NIOSH approved) when PEL/TLV is exceeded.

### OTHER PRACTICES

None

## SECTION 10 - TRANSPORTATION

<b>Shipping</b>	name Not regulated as a hazardous material for transport
<b>Labeling</b>	Not applicable
<b>Labeling Required</b>	None required
<b>Hazard Class</b>	Not applicable

## SECTION 11 - MISCELLANEOUS INFORMATION

### COMMENTS

Sand is applied as an anti-sticking agent to the membrane. Calcium carbonate is used as a compound stabilizer and is encased in the asphaltic matrix. Fibrous glass filaments are encapsulated in modified asphalt coating. Due to the nature of the specific use of these products, hazardous exposures are highly unlikely; however all relevant data has been provided for reference.

### ADDITIONAL INFORMATION

Contact TRI-BUILT® Materials Group at 800-516-1485

### MSDS REVISION SUMMARY

Revision Date	8/5/2014
Reason for Change	New format, Logo Updates

### DISCLAIMER

Information was obtained from sources, which we believe are reliable. However the information is provided without any representation or warranty, express or implied, regarding the accuracy or correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of or in any way connected with the handling, storage, use, or disposal of the product.