

TRI-BUILT[®] Modified SBS SA Base

SECTION 1: PRODUCT & COMPANY IDENTIFICATION

| | | | |
|------------------------|---|-----------------|---|
| PRODUCT NAME: | TRI-BUILT [®] SBS SA Base | Distributed By: | TRI-BUILT [®] Materials Group |
| CHEMICAL NAME: | Mixture | | |
| MANUFACTURER: | Polyglass USA, Inc. | ADDRESS: | 15 East Union Ave., East Rutherford, NJ 07073 |
| ADDRESS: | 1111 West Newport Center Drive, Deerfield Beach, FL 33442 | PHONE: | 1-800-516-1485 |
| PHONE: | (888) 410-1375 | INTERNET: | www.tribuiltmaterialsgroup.com |
| EMERGENCY PHONE: | 800-424-9300 Chemtrec | | |
| EFFECTIVE DATE: | 8/7/2014 | | |
| Signature of Preparer: | W. Rammacher / Allied Building Products Corp. | | |

SECTION 2 - PRODUCT INGREDIENT

| INGREDIENT NAME | COMMON NAME | CAS number | % Weight | Exposure Limit (OSHA) | Exposure Limit (ACGIH) |
|---------------------------------|------------------|---------------|-------------|--|--|
| Petroleum Asphalt | Asphalt | 8052 42 4 | 45.2 - 45.3 | 5 mg/m ³ PEL | 5 mg/m ³ TLV (as fume) |
| Calcium Carbonate | Limestone | 1317 65 3 | 18.1 - 19.7 | 5 mg/m ³ PEL (Respirable) 15 mg/m ³ PEL (Total) | 3 mg/m ³ TLV (Respirable) 10 mg/m ³ TLV (Total) |
| Styrene Butadiene Styrene | SBS Rubber | 9003-55-8 | 5.4 - 5.9 | Not established | Not established |
| Non-woven Polyester | Polyester mat | None assigned | 0 - 3.2 | Not established | Not established |
| Continuous Filament glass fiber | Fiberglass mat | 65997 17 3 | 0 - 1.8 | 5 mg/m ³ PEL (Respirable) 15 mg/m ³ PEL (Total) | 1 fiber/cc TLV 5 mg/m ³ TLV (Total) |
| Crystalline silica, Quartz | Sand | 14808 60 7 | 0 - 6.2 | 0.1 mg/m ³ PEL (Respirable) | 0.1 mg/m ³ TLV (Respirable) |
| Crushed Mineral | Roofing granules | None assigned | 21.6 - 23.3 | Not established | Not established |

SECTION 3 - PHYSICAL/CHEMICAL DATA

| PROPERTIES | UNIT | DATA |
|------------------------|---------|-----------------------------|
| Appearance | N/A | Black roll |
| Boiling point deg | F | >650 |
| Evaporation Rate | N/A | N/A |
| Flash Point | deg F | >430 |
| Melting Point | deg F | >220 |
| Odor | N/A | Mild asphalt/petroleum odor |
| Ph (undiluted product) | N/A | N/A |
| Saturation in air | % | N/A |
| Solids Content | N/A | N/A |
| Specific gravity | g/cc | 1.02 - 1.30 |
| Vapor Density | Air = 1 | N/A |
| Vapor Pressure | N/A | N/A |
| Viscosity | cP | N/A |
| VOC | g/liter | N/A |
| Volatility | % | < 0.1 |
| Water solubility | % | < 0.1 |

SECTION 4 - FIRE AND EXPLOSION DATA

| FLAMMABILITY PROPERTIES | |
|---|-----------------------|
| Flash point | >430 deg F (ASTM D92) |
| Lower Explosive | Limit Undetermined |
| Upper Explosive | Limit Undetermined |
| RECOMMENDED EXTINGUISHING MEDIA | |
| Dry chemical, foam, water fog, CO2 | |
| UNUSUAL FIRE OR EXPLOSION HAZARDS | |
| Burning will produce black smoke | |
| SPECIAL FIRE FIGHTING PROCEDURES | |
| Wear self contained breathing apparatus | |

SECTION 5 - HAZARD IDENTIFICATION

| ACUTE HEALTH EFFECTS | |
|--|--|
| Irritation of eye, nose, throat, and skin | |
| CHRONIC HEALTH EFFECTS | |
| Insufficient evidence of cancer induced by exposure to asphalt fumes. The International Agency for Research on Cancer (IARC) considered Crystalline Silica as a human carcinogen. Prolonged exposure to Crystalline Silica containing dust can lead to Silicosis. Continuous filament glass fibers are not classified as Carcinogens. However no significant health hazards are likely to occur due to the product form and nature of use. | |
| Upper respiratory system | |
| MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED | |
| Pre-existing respiratory conditions | |
| SIGNS/SYMPTOMS OF OVEREXPOSURE | |
| Inhalation | Headache, nausea, coughing, irritation of the upper respiratory system |
| Skin Contact | Burns caused by contact with hot material |
| Skin absorption | Not applicable |
| Ingestion | Not intended to be ingested |
| Eye Contact | Irritation/redness may occur |

SECTION 6 - FIRST AID PROCEDURES

| INHALATION |
|---|
| Remove affected person to fresh air |
| SKIN CONTACT |
| Rinse with cool water |
| SKIN ABSORPTION |
| Not applicable |
| INGESTION |
| Do not induce vomiting. Treat symptomatically. |
| EYE CONTACT |
| Flush with copious quantities of water. Consult a physician if irritation persists. |

SECTION 7 - STABILITY/REACTIVITY DATA

| SUMMARY |
|--|
| Material is stable. Hazardous polymerization will not occur. |
| CHEMICAL INCOMPATIBILITIES |
| Strong oxidizing agents, strong acids and alkalines. |
| CONDITION TO AVOID |
| Strong oxidizing agents at elevated temperatures and uncontrolled fumes. |
| THERMAL STABILITY |
| Stable |

SECTION 8 - HANDLING, USE AND DISPOSAL

| |
|--|
| PROCEDURES FOR SPILLS/LEAKS |
| Not applicable |
| WASTE DISPOSAL METHOD |
| Standard refuse disposal. Wastes are classified as non-hazardous by U. S. Environmental Protection Agency (EPA) and as per definition by Resource Conservation and Recovery Act (RCRA). Follow all local, state, and federal regulations governing waste disposal. Use protective equipment as described in Section IX. Keep away from heat or flame and protect from the elements. |
| HYGIENIC PRACTICE |
| Wash after any skin contact. |

SECTION 9 - EXPOSURE CONTROL/PERSONAL PROTECTION

| |
|---|
| EYE |
| Wear safety glasses with side shields. |
| SKIN |
| Wear leather or cotton gloves (impervious) |
| VENTILATION |
| Although normal conditions of product use does not warrant any special ventilation, use in well ventilated area. |
| RESPIRATORY |
| None required unless used with hot asphalt. Use breathing apparatus (only NIOSH approved) when PEL/TLV is exceeded. |
| OTHER PRACTICES |
| None |

SECTION 10 - TRANSPORTATION

| | |
|--------------------------|--|
| Shipping | name Not regulated as a hazardous material for transport |
| Labeling | Not applicable |
| Labeling Required | None required |
| Hazard Class | Not applicable |

SECTION 11 - MISCELLANEOUS INFORMATION

| |
|--|
| COMMENTS |
| Sand is applied as an anti-sticking agent to the membrane. Calcium carbonate is used as a compound stabilizer and is encased in the asphaltic matrix. Fibrous glass filaments are encapsulated in modified asphalt coating. Due to the nature of the specific use of these products, hazardous exposures are highly unlikely; however all relevant data has been provided for reference. |
| ADDITIONAL INFORMATION |
| Contact TRI-BUILT® Materials Group 800-516-1485 |
| MSDS REVISION SUMMARY |
| Revision Date: 8/5/2014 Reason for Change: New format, Logo Update |
| DISCLAIMER |
| Information was obtained from sources, which we believe are reliable. However the information is provided without any representation or warranty, express or implied, regarding the accuracy or correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of or in any way connected with the handling, storage, use, or disposal of the product. |