

TRI-BUILT® Seal Quik | White

SECTION 1: PRODUCT & COMPANY IDENTIFICATION

PRODUCT NAME:	TRI-BUILT® Seal Quik White	SUPPLIER:	TRI-BUILT® MATERIALS GROUP, LLC
PRODUCT CODE:	80450365	ADDRESS:	15 East Union Ave., East Rutherford, NJ 07073
CATEGORY:	PC9A Paints & Coatings	PHONE:	1-800-516-1485
MANUFACTURER:	Seymour of Sycamore, Inc	INTERNET:	www.tribuiltmaterialsgroup.com
ADDRESS:	917 Crosby Avenue		
PHONE:	Sycamore, IL 60178		
EMERGENCY PHONE:	Tel: 800-435-4482 Fax: 800-343-4258		
	CHEMTEL 1-800-255-3924, or 813-248-0585		
EFFECTIVE DATE:	2/19/2015		
Signature of Preparer:	W. Rammacher / Allied Building Products Corp.		

SECTION 2: HAZARD(S) IDENTIFICATION

Classification of the substance or mixture

- Flam. Aerosol 1 H222 Extremely flammable aerosol.
- Press. Gas H280 Contains gas under pressure; may explode if heated.
- Carc. 2 H351 Suspected of causing cancer.
- Repr. 2 H361 Suspected of damaging fertility or the unborn child.
- STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.
- Skin Irrit. 2 H315 Causes skin irritation.
- Eye Irrit. 2A H319 Causes serious eye irritation.
- STOT SE 3 H336 May cause drowsiness or dizziness.

GHS Hazard pictograms



Signal word

Hazard statements

Precautionary statements

Danger
 Extremely flammable aerosol.
 Contains gas under pressure; may explode if heated.
 Causes skin irritation.
 Causes serious eye irritation.
 Suspected of causing cancer.
 Suspected of damaging fertility or the unborn child.
 May cause drowsiness or dizziness.
 May cause damage to organs through prolonged or repeated exposure.
 If medical advice is needed, have product container or label at hand.
 Keep out of reach of children.
 Read label before use.
 Obtain special instructions before use.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Do not spray on an open flame or other ignition source.
 Pressurized container: Do not pierce or burn, even after use.
 Wash hands thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves/protective clothing/eye protection/face protection.
 Do not handle until all safety precautions have been read and understood.
 Wear protective gloves.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Call a poison center/doctor if you feel unwell.
 If skin irritation occurs: Get medical advice/attention.
 If on skin: Wash with plenty of water.
 If eye irritation persists: Get medical advice/attention.
 Take off contaminated clothing and wash it before reuse.
 Store locked up.
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 Store in a well-ventilated place. Keep container tightly closed.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 3: COMPOSITION INFORMATION ON INGREDIENTS

Chemical characterization: Mixtures

Chemical Description:

This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

1317-65-3	Calcium Carbonate	14.18%
64742-89-8	VM&P Naphtha	13.07%
74-98-6	propane	11.33%
142-82-5	heptane	10.78%
108-88-3	Toluene	10.72%
67-64-1	Acetone	9.19%
106-97-8	n-butane	6.66%
13463-67-7	titanium dioxide	4.73%
108-65-6	PM acetate	2.83%
1330-20-7	xylene (mix)	1.61%
64742-47-8	Mineral Spirits	1.1%

SECTION 4: FIRST AID MEASURES

After inhalation:

Supply fresh air; consult doctor in case of complaints.

After skin contact:

Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.

Most important symptoms and effects:

Dizziness

Indication of any immediate medical attention needed:

No further relevant information available.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Special hazards:

Can form explosive gas-air mixtures.

Protective equipment for firefighters:

A respiratory protective device may be necessary.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away. Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for containment and cleaning up:

Ensure adequate ventilation. Dispose contaminated material as waste according to section 13.

SECTION 7: HANDLING & STORAGE

**Precautions for safe handling
 Storage requirements:**

Use only in well ventilated areas. Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Components with limit values that require monitoring at the workplace:	
74-98-6 propane	
PEL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
TLV (USA)	refer to Appendix F
142-82-5 heptane	
PEL (USA)	Long-term value: 2000 mg/m ³ , 500 ppm
REL (USA)	Long-term value: 350 mg/m ³ , 85 ppm Ceiling limit value: 1800* mg/m ³ , 440* ppm *15-min
TLV (USA)	Short-term value: 2050 mg/m ³ , 500 ppm Long-term value: 1640 mg/m ³ , 400 ppm
108-88-3 Toluene	
PEL (USA)	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL (USA)	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV (USA)	Long-term value: 75 mg/m ³ , 20 ppm BEI
67-64-1 Acetone	
PEL (USA)	Long-term value: 2400 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 590 mg/m ³ , 250 ppm
TLV (USA)	Short-term value: (1782) NIC-1187 mg/m ³ , (750) NIC-500 ppm Long-term value: (1188) NIC-594 mg/m ³ , (500) NIC-250 ppm BEI
106-97-8 n-butane	
REL (USA)	Long-term value: 1900 mg/m ³ , 800 ppm
TLV (USA)	Short-term value: 2370 mg/m ³ , 1000 ppm
108-65-6 PM acetate	
WEEL (USA)	Long-term value: 50 ppm
1330-20-7 xylene (mix)	
PEL (USA)	Long-term value: 435 mg/m ³ , 100 ppm
REL (USA)	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV (USA)	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI

Ingredients with biological limit values:	
108-88-3 Toluene	
BEI (USA)	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)
67-64-1 Acetone	
BEI (USA)	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
1330-20-7 xylene (mix)	
BEI (USA)	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids

Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use. Avoid contact with the skin. Avoid contact with the eyes and skin. Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection: Protective gloves. The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Aerosol.
Odor:	Aromatic
Odor threshold:	Not determined.
pH-value:	Not determined.
Melting point/Melting range	Undetermined.
Boiling point:	-110 °C (-166 °F)
Flash point:	-19 °C (-2 °F)
Flammability (solid, gas):	Extremely flammable.
Decomposition temperature:	Not determined.
Auto igniting:	Product is not self-igniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit:	1.1 Vol %
Upper Explosion Limit:	10.9 Vol %
Vapor pressure:	Not determined.
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)
Vapour density	Not determined.
Evaporation rate	Not applicable.
Partition coefficient: n-octonal/water:	Not determined.
Solubility:	Not determined.
Viscosity:	Not determined.
VOC content:	561.1 g/l / 4.68 lb/gl
VOC content (less exempt solvents):	59.7 %
MIR Value:	1.15
Solids content:	30.8 %

SECTION 10 STABILITY AND REACTIVITY

Reactivity:	Stable at normal temperatures.
Conditions to avoid:	Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
Chemical stability:	Not fully evaluated.
Possibility of hazardous reactions:	No dangerous reactions known.
Incompatible materials:	No further relevant information available.
Hazardous decomposition:	No dangerous decomposition products known.

SECTION 11: TOXICOLOGICAL INFORMATION

LD/LC50 values that are relevant for classification:			
106-97-8 n-butane			
Inhalative	LC50/4 h	658 mg/l (rat)	
13463-67-7 titanium dioxide			
Oral	LD50	>20000 mg/kg (rat)	
Dermal	LD50	>10000 mg/kg (rbt)	
Inhalative	LC50/4 h	>6.82 mg/l (rat)	
108-65-6 PM acetate			
Oral	LD50	8500 mg/kg (rat)	
Inhalative	LC50/4 h	35.7 mg/l (rat)	
1330-20-7 xylene (mix)			
Oral	LD50	8700 mg/kg (rat)	
Dermal	LD50	2000 mg/kg (rbt)	
Inhalative	LC50/4 h	6350 mg/l (rat)	
Information on toxicological effects: No data available.			
Skin effects: Irritant to skin and mucous membranes.			
Eye effects: No irritating effect.			
Sensitization: No sensitizing effects known.			
Carcinogenic categories			
IARC (International Agency for Research on Cancer)			
108-88-3	Toluene		3
13463-67-7	titanium dioxide		2B
1330-20-7	xylene (mix)		3
NTP (National Toxicology Program)			
None of the ingredients is listed.			

SECTION 12: ECOLOGICAL INFORMATION

Aquatic toxicity: Hazardous for water, do not empty into drains.
Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.
Bioaccumulative potential: No further relevant information available.
Mobility in soil: No further relevant information available.
Other adverse effects: No further relevant information available.

SECTION 13: DISPOSAL CONSIDERATIONS

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.
Recommendation: Completely empty cans should be recycled.

SECTION 14: TRANSPORT INFORMATION

UN-Number UN1950
DOT Aerosols, flammable
ADR 1950 Aerosols, ENVIRONMENTALLY HAZARDOUS
Transport hazard class(es):
Class 2.1
Marine pollutant: Yes
 Symbol (fish and tree)
Special marking (ADR): Symbol (fish and tree)
Special precautions for user: Warning: Gases
EMS Number: F-D,S-U
Quantity limitations On passenger aircraft/rail: 75 kg
 On cargo aircraft only: 150 kg

ADR
Excepted quantities (EQ) Code: E0
 Not permitted as Excepted Quantity

IMDG

Limited quantities (LQ) 1L
Excepted quantities (EQ) Code: E0
 Not permitted as Excepted Quantity

Packaging Group: --
UN "Model Regulation": UN1950, Aerosols, ENVIRONMENTALLY HAZARDOUS, 2.1

SECTION 15: REGULATORY INFORMATION

SARA Section 355 (extremely hazardous substances):		
None of the ingredients in this product are listed.		
SARA Section 313 (Specific toxic chemical listings):		
108-88-3	Toluene	
1330-20-7	xylene (mix)	
CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.		
California Proposition 65 chemicals known to cause cancer:		
13463-67-7	titanium dioxide	
100-41-4	ethyl benzene	
California Proposition 65 chemicals known to cause developmental toxicity:		
108-88-3	Toluene	
67-56-1	Methanol	
CANADIAN ENVIRONMENTAL PROTECTION ACT: All hazardous ingredients for this product appear on the Canadian Domestic Substance List.		
EPA:		
142-82-5	heptane	D
108-88-3	Toluene	II
67-64-1	Acetone	I
1330-20-7	xylene (mix)	I

SECTION 16: OTHER INFORMATION

Contact: TRI-BUILT® Technical Department
Date of preparation / last revision 02/19/2015