

TRI-BUILT® ONE STEP MILLENNIUM Night Seal®

DESCRIPTION

TRI-BUILT® One Step Millennium Night Seal® is a highly elastomeric, solvent free, quick setting, foam sealer. The unique formulation results in a foam that has a weatherproof “skin”. TRI-BUILT® One Step Millennium Night Seal® sets in minutes, and is designed for use with our One Step application process.

Our One Step application process eliminates error due to poor mixing. Application is quick and easy, resulting in significant labor savings for the contractor. No expensive specialty pumps or spray rigs are required.

BASIC USE

TRI-BUILT® One Step Millennium Night Seal® is designed for use as a quick and reliable sealer at temporary tie-in locations between new roof covers and existing roof systems. TRI-BUILT® One Step Millennium Night Seal® eliminates the need for messy asphalt mastics and bitumens or less reliable porous surface foams.

SURFACE PREPARATION

All work surfaces should be clean, dry, and free of dirt, dust, debris, oils, loose and/or embedded gravel, un-adhered coatings, deteriorated membrane and other contaminants that may result in a surface that is not sound or is uneven.

STORAGE

Keep temperature of contents between 65°F-85°F (18°C-29°C) 24 hours prior to use. Do not store in direct sunlight or temperatures higher than 90°F (32°C).

COLOR

Black



FEATURES

- Ready to use
- No temperature restrictions
- One Step technology
- Solvent free
- Elastomeric
- Low rise foam
- Unique weatherproof “skin”

BENEFITS

- Requires no mixing, reduces labor costs
- Suitable for all climates
- Easy to apply
- VOC free, no odors
- Remains flexible, absorbs stresses
- Accommodates minor surface irregularities
- Waterproof tie-ins within minutes

SAFETY

Prior to working with this or any product consult product label and Safety Data Sheet (SDS) for necessary health and safety precautions.

LIMITATIONS

- Do not apply to wet or damp surfaces.
- Not intended for insulation attachment.

CAUTION: All statements and technical information in this document are based on tests or data that TRI-BUILT® MATERIALS GROUP, LLC believes is reliable. However, TRI-BUILT® MATERIALS GROUP, LLC does not warrant or guarantee the accuracy or completeness of this information. The user has sole knowledge and control of factors that can affect the performance of TRI-BUILT® MATERIALS GROUP, LLC products in the user's intended application. It is the user's responsibility to conduct tests to determine the compatibility of TRI-BUILT® MATERIALS GROUP, LLC product with the design, structure, and materials of the user's end product and the suitability of TRI-BUILT® MATERIALS GROUP, LLC product for the user's method of application and intended use. The user assumes all risk and liability arising out of such use.

APPLICATION

1. With utility knife, attach a mixing nozzle to the threaded mixing head.
2. Place the cartridge into the appropriate applicator.
3. Properly prepare existing membrane and/or substrate at temporary tie-in location. Surface to receive TRI-BUILT® One Step Millennium Night Seal® must be dry, clean, and free of loose material. All loose gravel must be removed.
4. Apply TRI-BUILT® One Step Millennium Night Seal® directly to the prepared substrate. Apply a continuous bead (minimum 3/4" width) approximately 1-1/2" from where the roof covers leading edge will fall. As the sealer is applied immediately place edge of the roof cover into the wet material. Do not allow the material to skin over.
5. Roll the outside edge of the roof cover to ensure positive contact with the substrate and to create a sufficient "bleed out" of sealer. TRI-BUILT® One Step Millennium Night Seal® will expand and seal the leading edge of the roof cover.
6. Un-used material can be applied at a later date by simply plugging the cartridges (with provided half moon plugs) and using a new mixing nozzle.

EQUIPMENT

The fast and dependable One Step applicators make applying TRI-BUILT® One Step Millennium Night Seal® simple:

- Battery Powered Single Bead
- Pneumatic Single Bead
- Stand Up Single Bead
- Ultra Drive Manual Applicator
- Heavy Duty Manual Applicator



PACKAGING & COVERAGE

TRI-BUILT® One Step Millennium Night Seal® is available in the following package:

Cartridge Size	Part #	Cartridges/Case
1.5 Liter	34950122	4

Covers 300 - 400 lin ft (91m - 122m) per case. Coverage rates are based on an application of one continuous ribbon approximately 3/4" (1.9cm) in width. Coverage rates will vary depending on surface conditions. Extremely irregular surfaces may require the use of a larger bead of material.

PRODUCT WARRANTY DISCLAIMER

TRI-BUILT® MATERIALS GROUP, LLC warrants its product(s) for a period of 2 years against manufacturing defects that directly result in leakage. In case of defect, TRI-BUILT® MATERIALS GROUP, LLC, at its sole option, will repair or replace the material, excluding the cost of labor to perform those tasks. TRI-BUILT® MATERIALS GROUP, LLC DISCLAIMS ALL IMPLIED WARRANTIES. Warranty coverage is an annually declining pro-rated warranty.