

TRI-BUILT® Sheathing Tape

OVERVIEW

TRI-BUILT® Sheathing Tape is an aggressive joint sealing tape well suited for reducing air infiltration through wall systems. TRI-BUILT® Sheathing Tape is compatible with most building & house wraps and poly-faced sheathing materials.

Another product in the TRI-BUILT® family of weatherization tools for the Residential and Commercial Applicant.

TYPICAL PROPERTIES

PROPERTY	RESULTS
Total Product Thickness	3.0 Mills
Peel Adhesion - Stainless Steel	65 oz/inch
Peel Adhesion - Polyethylene	16 oz/inch
Shear Strength	> 96 hours
Tensile Strength	20 lb/inch width
Elongation	136%
WVTR	0.16 g/100 in 2/24 hr
Application Temperature	-20° F to 120° F
Service Temperature	-40° F to 275° F

INSTALLATION GUIDELINES

Ensure that the wall substrate is flat and free of dust or moisture before TRI-BUILT® Sheathing Tape is applied. TRI-BUILT® Sheathing Tape has excellent cold weather adhesion and may be applied down to 10° F (12° C).

Apply TRI-BUILT® Sheathing Tape using firm, uniform pressure.

TRI-BUILT® Sheathing Tape must be covered within 90 days of initial application.

PROPERTY	SIZE
Roll Size	1 7/8" x 55 yards
Rolls/Case	16
Cases/Pallet	54

WARRANTY

TRI-BUILT® MATERIALS GROUP, LLC believes the information and recommendations herein to be accurate and reliable. However, since use and conditions are not within its control, TRI-BUILT® MATERIALS GROUP, LLC does not guarantee results from the use of such products or other MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OTHERWISE WITH RESPECT TO THE PRODUCTS REFERRED TO