

# TRI-BUILT® #30 Asphalt Felt – ASTM D 226

## PRODUCT DESCRIPTION:

TRI-BUILT® #30 ASTM D 226 is a widely accepted underlayment product that is manufactured from superior quality organic felt that is saturated with asphalt. Line markings are placed on the top surface at 2", 8 ½", 11 5/16", and 17" from each side of the sheet.

## PRODUCT USE:

**TRI-BUILT® #30 – ASTM D 226** underlayment is applied over the roofing deck before installation of asphalt shingles. This product is highly recommended as an underlayment for architectural shingles and is not recommended for 20 year 3 tab shingles.

## TECHNICAL DATA:

### ASTM D 226 Type II

Width of roll	36"
Roof coverage per roll	216 sq ft
Mass of saturated felt roll	26 lbs./ 100 ft. sq.
Mass of asphalt saturant	15 lbs. / 100 ft. sq.
Mass of desaturated felt	10 lbs. / 100 ft. sq.
Max ash	10%
Average (min.) breaking strength	
Machine direction	40 lbf/in
Cross direction	20 lbf/in
Pliability at 77 ° F when bend 90°	¾" radius
Max. loss on heating at 221° F	4%

### PACKAGING:

Pallet size	42" x 48"
Rolls per pallet	25 - 2 square rolls
Pallets per truck	36