

# TRI-BUILT® #30 Asphalt Felt – ASTM D 4869

## PRODUCT DESCRIPTION:

**TRI-BUILT® #30 – ASTM D 4869** is a widely accepted underlayment product that is manufactured from organic felt and is saturated with asphalt. Line markings are placed on the top surface at 2", 8 ½", 11 5/16", and 17" from each side of the sheet.

## PRODUCT USE:

**TRI-BUILT® #30 – ASTM D 4869** underlayment is applied over the roofing deck before installation of asphalt shingles. This product is highly recommended as an underlayment for architectural shingles and is not recommended for 20 year 3 tab shingles.

## TECHNICAL DATA:

### ASTM D 4869 Type II

Width of roll	36"
Roof coverage per roll	216 sq ft
Mass of saturated felt roll	13 lbs. / 100 ft. sq.
Mass of asphalt saturant	6.0 lbs. / 100 ft. sq.
Mass of desaturated felt	5.0 lbs. / 100 ft. sq.
Saturation by weight (min)	100%
Saturation efficiency (min) by weight	75%
Breaking strength at 77F (min)	
Machine direction	30 lbf/in
Cross direction	15 lbf/in
Pass 4 hour liquid transmission water test	YES
Pliability at 77F when bend 90 degrees	½" radius

## PACKAGING:

Pallet size	42" x 42"
Rolls per pallet	25 - 2 square rolls
Pallets per truck	32