

TRIBUILT® MULTI PURPOSE SEALANT

The next generation multi-purpose sealant that adheres to any surface, with the flexibility and durability to hold up under the most demanding conditions. Due to it's thermoplastic elastomer base, this sealant will not crack in cold temperatures, is impervious to water, and protects substrates in corrosive environmental conditions. It can also be top coated with oil or latex paints.

BENEFITS:

- Does not lose flexibility
- Protects against UV light
- Resists temperature extremes
- Impervious to water
- Abrasion resistant

SUGGESTED USES:

- Skylights
- Flashings
- Air Vents
- Driveway and sidewalk cracks
- Gutters
- Shingles



WHITE



BLACK



CLEAR

Additional Information:

This product leaves a slightly bubbly film. When covering a broad area it is recommended that two coats be applied to ensure a non-porous final coating. Allow first coat to dry to touch (about 8-10 minutes) before applying the second and final coat.

Properties:		Dry Time*:		Packaging:	
Flammability	"Extremely Flammable"	To touch	10 minutes	Cans per case	12
Flash point	-40 F	To topcoat	30 minutes	Shipping weight per case	19 lbs.
Specific Gravity	0.80			Container	20 fluid ounce can
Solids Content	~13%			Label weight	15 ounces (425 grams)
VOC content	~46%, cannot exceed 60%	*At 72° F, 50% humidity,		Shipping Classification	Consumer Commodity
MIR value	~1.15, cannot exceed 1.20	1.5 mil thickness		Hazard Class	ORM-D UN 1950
HAPs content	~10%	**Curing/Recoat time is extended with			2.1
Storage Temperature	40-100F	multiple coats and excessively thick			
Application Temperature	50-90F	coats**			
Durability	Good				
Abrasion Resistance	Good				
Heat Resistance	250° F				
Resin System	Phenolic	Gloss*:	Flat, <15		
Shelf life	Guaranteed for 2 years		*as measured on a 600 gloss meter		
Food contact rating	No				