



MATERIAL SAFETY DATA SHEET

Page 1 of 7

AP200WG - TRI-BUILT WET/DRY PLASTIC ROOF CEMENT - WINTER GRADE

1. Product And Company Identification

Supplier TRI-BUILT Roofing Products 15 East Union Avenue PO Box 511 East Rutherford, NJ 07073 Telephone Number: 800-516-1485	Manufacturer TRI-BUILT Roofing Products 15 East Union Avenue PO Box 511 East Rutherford, NJ 07073 Telephone Number: 800-516-1485
Supplier Emergency Contacts & Phone Number CHEMTREC: 800-424-9300	Manufacturer Emergency Contacts & Phone Number CHEMTREC: 800-424-9300

Issue Date: 02/26/2010

Product Name: AP200WG - TRI-BUILT WET/DRY PLASTIC ROOF CEMENT - WINTER GRADE

Product Code: AP200WG

2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
1,2,4-trimethylbenzene	95-63-6	0.1 - 1
1,3,5-trimethylbenzene	108-67-8	0.5 - 5
petroleum asphalt	8052-42-4	30 - 60
attapulgite	12174-11-7	3 - 7
calcium carbonate	1317-65-3	10 - 30
cellulose fiber	9004-34-6	3 - 7
diesel fuel no. 2	68476-34-6	0 - 10
silica, quartz	14808-60-7	0.5 - 1.5
stoddard solvent	8052-41-3	10 - 30
xylene	1330-20-7	0.1 - 1

EMERGENCY OVERVIEW

CAUTION! Combustible Liquid. Central nervous system depressant. Vapor may cause light-headedness, headache, nausea, loss of coordination and respiratory tract irritation. Causes skin irritation.

Appearance/Odor: Black liquid, strong petroleum solvent odor

3. Hazards Identification

Primary Routes(s) Of Entry

Inhalation, Skin Contact

Eye Hazards

May cause eye irritation (burning, tearing, redness or swelling).

Skin Hazards

May cause skin irritation and contact dermatitis upon prolonged contact. Prolonged contact with liquid may cause dermal absorption.

Ingestion Hazards

May be harmful if swallowed. May cause gastric distress, vomiting and diarrhea.



MATERIAL SAFETY DATA SHEET

Page 2 of 7

AP200WG - TRI-BUILT WET/DRY PLASTIC ROOF CEMENT - WINTER GRADE

3. Hazards Identification - Continued

Inhalation Hazards

Exposure to vapors, dusts or mists may cause respiratory tract irritation. Inhalation of vapors or mists may cause central nervous system depression, light-headedness, headache, nausea and loss of coordination.

Chronic/Carcinogenicity Effects

This product or one of its ingredients present at 0.1% or more is listed as a carcinogen by NTP, IARC or OSHA. See Section 11 (Toxicological Information) for more details.

4. First Aid Measures

Eye

In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

Skin

Remove contaminated clothing and shoes. Wash affected areas with soap and water.

Ingestion

Get medical attention immediately. DO NOT INDUCE VOMITING. Never give anything by mouth to an unconscious victim. Call a physician or poison control center immediately.

Inhalation

Remove the person from the contaminated area to fresh air. If breathing is difficult, give oxygen. Get medical attention immediately.

Note To Physician

Aspiration of liquid into the lungs during swallowing or vomiting can cause lung inflammation, serious lung damage and even death from chemical pneumonitis.

5. Fire Fighting Measures

Flash Point: 105 °F

Flash Point Method: Closed Cup

Lower Explosive Limit: 0.9

Upper Explosive Limit: 6.0

Fire And Explosion Hazards

Combustible Liquid. Vapors are heavier than air and may spread long distances and ignite. Thermal decomposition (burning) may release irritating, corrosive and/or toxic gases, vapors and fumes.

Extinguishing Media

Chemical foam, carbon dioxide (CO₂), or dry chemical. Do not use direct stream of water.

Fire Fighting Instructions

Firefighters should wear self-contained breathing apparatus and full protective gear.

6. Accidental Release Measures

Contain and/or absorb spill with inert material (e.g. sand, vermiculite). Collect and dispose in accordance with applicable regulations. Avoid runoff to waterways and sewers. For large spills, contain runoff and recover by pumping with explosion proof equipment.

7. Handling And Storage

Handling And Storage Precautions

Keep away from ignition sources. Keep containers tightly closed. Store in a cool, dry, well-ventilated area. Do not handle or store near heat, sparks, flame, strong oxidants or strong acids. Use only with adequate ventilation.



AP200WG - TRI-BUILT WET/DRY PLASTIC ROOF CEMENT - WINTER GRADE

8. Exposure Controls/Personal Protection

Engineering Controls

Use with adequate general and local exhaust ventilation. When used outdoors, stay well away from building air intakes or close and seal the intakes to prevent product from entering building.

Eye/Face Protection

Safety glasses with side shields or goggles recommended.

Skin Protection

Use with chemical-protective gloves to prevent skin contact.

Respiratory Protection

This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.

The level of respiratory protection needed should be based on the evaluation of chemical exposures by a health or safety professional. If required, use a NIOSH-approved air purifying respirator with organic vapor cartridge and particulate filter or supplied air respirator.

Occupational Exposure Limits for individual ingredients (if available) are listed below.

Ingredient(s) - Exposure Limits

1,2,4-trimethylbenzene

ACGIH TLV-TWA 25 ppm

1,3,5-trimethylbenzene

ACGIH TLV-TWA 25 ppm

petroleum asphalt

ACGIH TLV-TWA 0.5 mg/m³ (inhalable fraction, as benzene-soluble aerosol)

calcium carbonate

OSHA PEL-TWA 15 mg/m³ (total dust)

OSHA PEL-TWA 5 mg/m³ (respirable dust)

cellulose fiber

ACGIH TLV-TWA 10 mg/m³

diesel fuel no. 2

ACGIH TLV-TWA 100 mg/m³ (as total hydrocarbons)

silica, quartz

ACGIH TLV-TWA 0.025 mg/m³

OSHA PEL-TWA 30mg/m³ / (%SiO₂+2) (total dust)

OSHA PEL-TWA 10 mg/m³/ (%SiO₂+2) (respirable dust)

stoddard solvent

ACGIH TLV-TWA 100 ppm

OSHA PEL-TWA 500 ppm

xylene

ACGIH TLV-STEL 150 ppm

ACGIH TLV-TWA 100 ppm

OSHA PEL-TWA 100 ppm

9. Physical And Chemical Properties

Appearance

Black Liquid

Odor

Strong Petroleum Solvent Odor

Chemical Type: Mixture



MATERIAL SAFETY DATA SHEET

Page 4 of 7

AP200WG - TRI-BUILT WET/DRY PLASTIC ROOF CEMENT - WINTER GRADE

9. Physical And Chemical Properties - Continued

Boiling Point: 300-800 °F
Specific Gravity: 0.97
Percent Volatiles: <26
Vapor Pressure: 2@68°F
Vapor Density: >1
pH Factor: not applicable
Solubility: insoluble in water
Evaporation Rate: <1

10. Stability And Reactivity

Stability: Stable
Hazardous Polymerization: Will not occur

Incompatible Materials

Avoid contact with strong oxidizing agents and acids.

Hazardous Decomposition Products

Toxic and irritating gases, vapors or fumes, carbon monoxide (CO), carbon dioxide (CO₂).

11. Toxicological Information

Chronic/Carcinogenicity

IARC has concluded that the following chemicals in this product are carcinogenic to humans (Group 1): silica, quartz
ACGIH has designated the following chemicals in this product as suspected human carcinogens (A2): silica, quartz
ACGIH has designated the following chemicals in this product as confirmed animal carcinogens with unknown relevance to humans (A3): diesel fuel no. 2
NTP has listed the following chemicals in this product as known human carcinogens: silica, quartz
Risk of cancer depends on duration and level of exposure to this product as a dust or aerosol mist.

Miscellaneous Toxicological Information

Toxicological testing has not been conducted for this product overall. Available toxicological data for individual ingredients are summarized below.

Ingredient(s) - Toxicological Data

1,2,4-trimethylbenzene
LD50 (oral, rat): 5000 mg/kg
LC50 (rat): 18 g/m³ (4-hour exposure)
1,3,5-trimethylbenzene
Lethal dose (oral, rat): 23 g/kg lethal to 7 of 10 test animals
LC50 (rat): 24 g/m³ (4-hour exposure)
calcium carbonate
oral-rat LD50: 6450 mg/kg
cellulose fiber
LD50 (oral, rat): >2000 mg/kg
LC50 (rat): >5800 mg/m³ (4-hour exposure)
silica, quartz
iv-rat LD50: 500 mg/kg bw/Quartz (10-200 um)
stoddard solvent
oral-rat LD50: >5000 mg/kg
dermal-rabbit LD50: >3000 mg/kg

AP200WG - TRI-BUILT WET/DRY PLASTIC ROOF CEMENT - WINTER GRADE

11. Toxicological Information - Continued

Ingredient(s) - Toxicological Data - Continued

inhal-rat LC50: >5500 mg/m³ (880 ppm)

inhal-rat LC50: >1300 ppm

xylene

LD50 (oral, rat): 5400 mg/kg

LD50 (dermal, rabbit): 12180 mg/kg

LC50 (rat): 6350 ppm (4-hour exposure)

12. Ecological Information

No specific information available.

13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations.

14. Transport Information

Ground or Water Domestic Voyage

Not restricted if shipped in containers <450L (119 gallons)

Restricted if shipped in containers >450L (119 gallons)

US NA1993, Combustible liquid, n.o.s., (Petroleum Distillates mixture), Combustible liquid, III

Canada UN1999, Tars liquid, 3, III

Unless departs >flash point:

Both UN3256, Elevated Temperature liquid, flammable, n.o.s., (Petroleum Distillates mixture), 3, III

IMDG IMDG Code 2.3.2.5 - exempted from marking, labeling & testing of packages

IATA UN1999, Tars liquid, 3, III

DOT (Pictograms)



15. Regulatory Information

U.S. Regulatory Information

Asphalt may contain detectable amounts of chemicals known to the State of California to cause cancer or reproductive harm.

Ingredient(s) - U.S. Regulatory Information

1,2,4-trimethylbenzene

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical

xylene

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical

Ingredient(s) - State Regulations

1,2,4-trimethylbenzene

New Jersey - Workplace Hazard

New Jersey - Environmental Hazard

Massachusetts - Hazardous Substance

New York City - Hazardous Substance



AP200WG - TRI-BUILT WET/DRY PLASTIC ROOF CEMENT - WINTER GRADE

15. Regulatory Information - Continued

Ingredient(s) - State Regulations - Continued

- 1,3,5-trimethylbenzene
 - New Jersey - Workplace Hazard
 - Massachusetts - Hazardous Substance
 - New York City - Hazardous Substance
- petroleum asphalt
 - New Jersey - Workplace Hazard
 - Pennsylvania - Workplace Hazard
 - Massachusetts - Hazardous Substance
 - New York City - Hazardous Substance
- attapulgate
 - California - Proposition 65
- calcium carbonate
 - Pennsylvania - Workplace Hazard
- cellulose fiber
 - Pennsylvania - Workplace Hazard
- silica, quartz
 - New Jersey - Workplace Hazard
 - Pennsylvania - Workplace Hazard
 - California - Proposition 65
 - Massachusetts - Hazardous Substance
- stoddard solvent
 - New Jersey - Workplace Hazard
 - Pennsylvania - Workplace Hazard
 - Massachusetts - Hazardous Substance
 - New York City - Hazardous Substance
- xylene
 - New Jersey - Workplace Hazard
 - New Jersey - Environmental Hazard
 - New Jersey - Special Hazard
 - Pennsylvania - Workplace Hazard
 - Pennsylvania - Environmental Hazard
 - Massachusetts - Hazardous Substance
 - New York City - Hazardous Substance

Canadian Regulatory Information

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR. WHMIS Classification: B3 - Combustible Liquid, D2A - Very Toxic

Ingredient(s) - Canadian Regulatory Information

- 1,2,4-trimethylbenzene
 - WHMIS - Ingredient Disclosure List
- 1,3,5-trimethylbenzene
 - WHMIS - Ingredient Disclosure List
- silica, quartz
 - WHMIS - Ingredient Disclosure List
- stoddard solvent
 - WHMIS - Ingredient Disclosure List





MATERIAL SAFETY DATA SHEET

Page 7 of 7

AP200WG - TRI-BUILT WET/DRY PLASTIC ROOF CEMENT - WINTER GRADE

WHMIS - Canada (Pictograms)



NFPA	HMIS								
	<table border="1"><tr><td>HEALTH</td><td>1</td></tr><tr><td>FLAMMABILITY</td><td>2</td></tr><tr><td>REACTIVITY</td><td>0</td></tr><tr><td>PERSONAL PROTECTION</td><td></td></tr></table>	HEALTH	1	FLAMMABILITY	2	REACTIVITY	0	PERSONAL PROTECTION	
HEALTH	1								
FLAMMABILITY	2								
REACTIVITY	0								
PERSONAL PROTECTION									

16. Other Information

Revision/Preparer Information

This MSDS Supersedes A Previous MSDS Dated: 02/26/2010

Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).