

TRI-BUILT® High Performance Underlayment

TRI-BUILT® High Performance Underlayment is a premium synthetic underlayment which is among the safest, strongest, and best-performing roof underlayments on the market. It balances strength and weight, provides dynamic steep-slope traction, and will not buckle, warp or crack. High Performance Underlayment is rated for commercial and residential applications using plastic cap fasteners and roofing nails (3/8-inch head), and is an ideal underlayment for asphalt shingles, metal, tile, slate and a variety of sloped roofing materials. Skid-resistant, textured surfaces make TRI-BUILT® the best choice for steep slope applications. Here's why:

- Best substitute for 30 lb. organic felt
- Stronger than 30 lb felt and resistant to tearing and stretching around fasteners and high traffic areas or during high winds
- Faster installation, better installed performance
- 5x more coverage per roll than 30 lb felt
- Regular Roofing Nails, Caped Nails or Capped Staples – less nails needed – less labor
- 10 square roll – goes down faster – less labor
- Best looking custom printing for a modest upcharge
- Cool Grey color to reduce heat build-up on hot days
- Less weight per roll makes it easier to handle during all stages of installation
- Great for asphalt shingles, metal, tile, slate applications
- 6 month exposure time
- 50 year limited warranty

Specifications	TRI-BUILT High Performance Underlayment	30# Conventional Felt
Composite Material	Woven Synthetic	Asphalt
Width Per Roll	48"	36"
Length Per Roll	250 ft	72 ft
Weight Per Roll	32 lbs	32 lbs to 60 lbs
Roll Size	10 sq.	2 sq
Rolls Per Pallet	36	30
Permeability	.14 ASTM96	1.75 perms
Water Transmission	PASS - ASTM4869	PASS - ASTM4869
Tear Strength	MD 36 / CD 22	MD 4 lbs / CD 2 lbs
Tensile Strength	MD 120 / CD 80	MD 70 lbs / 38 lbs
UV-Resistant	Yes - Up to 6 Months	NO
Class A Fire Rated	Yes	NO
Pre-Printed Nailing Pattern	Yes	NO
Temperature Range	266F	N/A
Warranty	50 YEAR	NONE