

TR4BUILT
TRI-BUILT® MATERIALS GROUP, LLC
CUTTINGEDGEII
REPLACEMENT WINDOWS - PRO SERIES



SLIDING WINDOWS

Panoramic vistas meet ultimate convenience with our sliding windows. Their undeniable beauty is matched only by their superior thermal performance, letting you enjoy your view ever so comfortably. Available sliding window configurations include two- and three-lite configurations. Three-lite configurations available in 1/4-1/2-1/4 lite and 1/3-1/3-1/3 equal lite.



SLIDING WINDOW

STANDARD FEATURES

- New Generation uPVC vinyl never needs painting or caulking and resists conducting heat and cold
- State-of-the-art track and adjustable roller system for easy gliding
- Ventilation limit-latch standard: optional child safety vent latch
- Sleek, low-profile design, cam-action locks on windows over 25" tall
- Fusion-welded sash and frames stay strong and in place for a lifetime of dependable performance
- In-home removable sash for safe, easy cleaning
- 7/8" insulating glass with InsulEdge spacer system for added energy efficiency
- Integral interlock and dual fin and pile weatherstripping on both sash and mainframe for protection against air, dust and moisture
- Trim line design for maximum viewing area
- Extruded aluminum half screen with fiberglass mesh



OPTIONAL FEATURES

- Glass package options: Insulated glass unit with one lite of Low-E or Low-E^{SC} (solar-cooling) glass and air fill; Performance Glass (PG) insulated glass unit with single lite of Low-E or Low-E^{SC} glass with argon gas; PG2-X triple pane unit/2 lites Low-E/argon; PG3-X triple pane unit with two lites of Low-E and one lite of interior surface Low-E glass/argon
- Performance upgrade options: InsulEdge+ nonconductive spacer system; X-Core foam insulation in the frame
- Screen options: Optimal viewing, solar block, aluminum mesh. Optional full screen available
- Additional glass options: Advanced Easy Clean, tinted, double strength, obscure, glue chip obscure, tempered, laminated (security), or sound package (off-set glass)



COLOR OPTIONS:

	INTERIOR		EXTERIOR		INTERIOR	EXTERIOR
	WHITE	WHITE	EARTHTONE	DARK BRONZE	BEIGE	BEIGE
		BEIGE	SANDSTONE			

GRILLE OPTIONS: GRILLES-BETWEEN-THE-GLASS

5/8" Flat Colonial	5/8" Flat Diamond	5/8" Flat Perimeter	1 1/16" Sculptured Colonial	1" Sculptured Colonial



TRI-BUILT® CUTTINGEDGE II PRO REPLACEMENT WINDOWS HAVE BEEN GREEN APPROVED BY THE NAHB RESEARCH CENTER.

This means you can be assured that TRI-BUILT® CUTTINGEDGE II PRO Replacement windows comply with specific green practice criteria in the National Green Building Standard.

Visit www.GreenApprovedProducts.com for more details.

1. PG-X glass packages are triple pane insulated glass units with argon. See sidebar above for specific details.
 2. Optional frame X-Core insulation available in double hung, sliding, fixed, casement and awning windows.
 3. Most sliding windows meet a Design Pressure (DP) rating of 30.

* Colors are reproduced as accurately as printer technology allows. Please see your authorized TRI-BUILT® CUTTINGEDGE II representative for actual samples.