

RXT 900

SECTION 1: PRODUCT & COMPANY IDENTIFICATION

PRODUCT NAME:	ROOF X TENDER RXT 900	Distributed By:	TRI-BUILT® Materials Group, LLC
CHEMICAL NAME:	Elastomeric SB		
MANUFACTURER:	Gardner Asphalt Corporation	ADDRESS:	P.O. Box 70, Rutherford, NJ 07070
ADDRESS:	P.O. Box 5449	PHONE:	1-800-516-1485
PHONE:	Tampa, Florida 33675-5449	INTERNET:	www.tribuiltmaterialsgroup.com
EMERGENCY PHONE:	800-424-9300 CHEMTREC		
EFFECTIVE DATE:	10/12/2015		
Signature of Preparer:	W. Rammacher / Allied Building Products Corp.		

SECTION 2: HAZARDS IDENTIFICATION

INGREDIENT	PERCENT	TLV PPM	PEL-TWA PPM
XYLENE CAS # - 1330-20-7	<52	NA	100
TITANIUM DIOXIDE CAS #- 13463-67-7	<12	NA	NA
ZINC OXIDE CAS #- 1314-13-2	<1	NA	NA
POLY STYRENE CAS #- 66070-58-4	<21	NA	NA

N.E.= Not Established

SECTION III – PHYSICAL DATA

BOILING RANGE: 137 °F - 278°F	VAPOR DENSITY <input checked="" type="checkbox"/> HEAVIER	<input type="checkbox"/> LIGHTER, THAN AIR
VAPOR PRESSURE: ~9mm @ 68°F	Appearance:Clear	Odor:Mild
EVAPORATION RATE <input type="checkbox"/> FASTER	<input checked="" type="checkbox"/> SLOWER, THAN	PERCENT VOTILE BY
	ETHER	VOLUME 56 %
SOLUBILITY IN WATER: None	PHYSICAL STATE :Liquid	WEIGHT PER GALLON
		BY VOLUME 8.47.2 LBS
		Ph: NA

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

FLASH POINT=80 F	EXPLOSION HAZARD:Not Applicable
LEL-0.6 UEL 4.2	
EXTINGUISHING MEDIA-	CARBON DIOXIDE, FOAM, & DRY CHEMICAL
UNUSUAL FIRE AND EXPLOSION HAZARDS-	CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED
TO EXTREME HEAT. PRODUCTS OF COMBUSTION MAY BE TOXIC	
SPECIAL FIRE FIGHTING PROCEDURES-	WEAR SELF CONTAINED BREATHING APPARATUS.
WATER MAY BE USED TO COOL CLOSED CONTAINERS. HIGH PRESSURE STREAM WILL SPREAD FIRE.	

SECTION V – REACTIVITY DATA

STABILITY: <input type="checkbox"/> UNSTABLE	<input checked="" type="checkbox"/> STABLE	CONDITIONS TO AVOID: STORE AWAY FROM
		STRONG OXIDIZING MATERIALS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: STORE IN A COOL, DRY PLACE. KEEP CONTAINER CLOSED WHEN NOT IN USE. PROTECT FROM FREEZING.

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON OXIDES AND TRACES OF INCOMPLETELY BURNED CARBON COMPOUNDS.

HAZARDOUS POLYMERIZATION: MAY OCCUR WILL NOT OCCUR

SECTION VI-HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE:

ACUTE EFFECTS: SKIN: May cause slight irritation to sensitive skin. INHALATION: Overexposure may cause dizziness

INGESTION May cause nausea, consult physician immediately.

CHRONIC EXPOSURE EFFECTS: SKIN: No known applicable information INHALATION: No known applicable information INGESTION: None known.

EMERGENCY FIRST AID PROCEDURE-

EYES: Flush with water for 15 minutes. Get medical attention if irritation persists.

SKIN: Wash with soap and water or waterless cleanser. Get medical attention if irritation develops or persists.

INHALATION: If symptoms develop, move to fresh air.

INGESTION: Don not induce vomiting. If symptoms develop, seek medical advice from a physician. No ingredient in this product is an IRAC, NTP or OSHA listed carcinogen.

SECTION VII – SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Observe all personal protection equipment recommendations described in Section VIII. Wipe up spill and contain for disposal. Final cleaning may require use of hot water and/or detergents. Dispose of saturated absorbent or cleaning materials appropriately

WASTE DISPOSAL METHOD: Dispose of unused material in accordance with Federal, State, and Local Regulations.

SECTION VIII – SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Use with adequate ventilation.

SKIN PROTECTION: Protective gloves are recommended for prolonged exposure.

EYE PROTECTION: Safety glasses with side shields.

OTHER PROTECTIVE EQUIPMENT: None

DOT Description Xylene, 3, UN1307, III

SECTION IX – OTHER INFORMATION

OTHER PRECAUTIONS: KEEP OUT OF THE REACH OF CHILDREN. KEEP CONTAINER CLOSED WHEN NOT IN USE. PROTECT FROM FREEZING.

TSCA Status: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

Hazardous Materials Identification System (HMIS)

Health	Flammability	Reactivity	Personal Protection
1	3	0	D

Prepared By:

Barton Malina