

## TRI-BUILT® CUTTINGEDGE Architectural Access Door


TRI-BUILT® CUTTINGEDGE Architectural Access Door is built with the architect in mind. Constructed with an industry-standard 14 gauge steel door, the updated design further improves on strength and aesthetics.

- DOOR: 14 gauge cold rolled steel or 16 gauge T304 Stainless Steel
- FRAME: 16 gauge cold rolled steel or 16 gauge T304 Stainless Steel
- HINGE: Concealed spring button
- PAN DEPTH: 1/2"
- FINISH: White powder paint or Mill
- OPTIONS: Flanges, Latches, Gaskets, Masonry Anchors and Stainless Steel




TBNTC1212

### Features




#### Anti-flex frame

Screws are inserted through our patent-pending Easy Install Tabs, firmly fitting the door to the wall without flexing the frame.



#### Painless installation

When mounting screws are not required, quickly and easily install your new panel by bending our patent-pending Easy Install Tabs over the drywall.



#### Optional stainless steel

The spot free design on the face of the door gives an aesthetically pleasing appearance.

**TBN**  FLANGE  LATCH  WIDTH X  HEIGHT  OPTIONS

FLANGE	
T	1" Flange
W	Drywall bead
P	Plaster casing

LATCH	
C	Screwdriver cam latch
L	Key operated cam latch
M	Mortise lock (1-1/8") prep
N	Knurled Knob


STANDARD SIZES (WIDTH & HEIGHT)					
6" x 6"	12" x 24"	18" x 24"	24" x 30"	32" x 32"	
8" x 8"	14" x 14"	20" x 30"	24" x 36"	36" x 36"	
10" x 10"	16" x 16"	22" x 22"	24" x 48"	36" x 48"	
12" x 12"	16" x 20"	22" x 30"	30" x 30"		
12" x 18"	18" x 18"	24" x 24"	30" x 36"		

OPTIONS	
S	T304 Stainless Steel
B	Bonderized / galvanized
G	Gasketing
M	Masonry anchors


*Rough opening is door size + 1/4".*

# OPTIONS

## MATERIALS




**B Galvanized / bonderized steel**  
with primer coat. Use where corrosive resistance is required.



**S Stainless steel type #304**  
Extremely resistant to corrosion. With #4 satin polish finish.

## ADDITIONAL OPTIONS



**G Gasketing**  
Applied to the doorstops for weather resistance. Also available with UL listed smoke seal.



**M Masonry anchors**  
Attached to the frame to secure the panel when installed in masonry.

## HINGE OPTIONS



**H Continuous piano hinge**  
Provides specification compliance when required.



**Z Concealed continuous piano hinge**  
Provides added security while maintaining superior aesthetics.


## FLANGES



1" Flange



Drywall bead



Plaster bead

## LATCH & LOCK OPTIONS



**C Screwdriver operated cam latch**  
Most common. Appropriate for standard applications.



**N Knurled knob cam latch**  
Unrestricted access – no tool required. Finger operated.



**K Knurled knob/key operated latch bolt**  
Patented ball bearing latch bolt operated by a screw-in type knurled knob or flush key.



**L Key operated cam lock**  
Provides an economical solution for controlled access when locks are required.



**M Mortise cylinder lock preparation**  
Very secure. Matches project hardware. Accepts standard 1.125" mortise cylinder.

## POWDER COATING OPTIONS




White

Note: White is the base color, all other colors have additional charges and may require longer lead times.


Colors shown give only an indication of shade. Samples are available upon request.



FP1  
ANSI 70  
Gray



FP43  
Traffic  
White



FP44  
High Reflectance  
White