

TRI-BUILT® CUTTINGEDGE Restoration Access Door


TRI-BUILT® CUTTINGEDGE Restoration Access Door is lighter gauge alternative to the Architectural Door. The panel features an industry-leading design to provide superior durability and functionality.

DOOR: 20 gauge cold rolled steel
 FRAME: 20 gauge cold rolled steel
 HINGE: Concealed spring button
 PAN DEPTH: 1/2"
 FINISH: White powder paint




TBETC1212

Features




Anti-flex frame

Fasteners are inserted through our patent-pending Easy Install Tabs, firmly fitting the door to the wall without flexing the frame.



Painless installation

When fasteners are not required, quickly and easily install your new panel by bending our patent-pending Easy Install Tabs over the drywall.



A lighter gauge alternative

With all of the same features of the TRI-BUILT® CUTTINGEDGE Architectural Access Door, the Renovation Door is a perfect complement for applications where a lighter material gauge is acceptable.

TBE

FLANGE

LATCH

WIDTH

 X

HEIGHT

OPTIONS

FLANGE	
T	1" Flange
W	Drywall bead

LATCH	
C	Screwdriver cam latch
L	Key operated cam latch
N	Knurled Knob


STANDARD SIZES (WIDTH & HEIGHT)				
6" x 6"	12" x 24"	18" x 24"	24" x 30"	32" x 32"
8" x 8"	14" x 14"	20" x 30"	24" x 36"	36" x 36"
10" x 10"	16" x 16"	22" x 22"	24" x 48"	
12" x 12"	16" x 20"	22" x 30"	30" x 30"	
12" x 18"	18" x 18"	24" x 24"	30" x 36"	

OPTIONS	
B	Bonderized / galvanized
G	Gasketing


Rough opening is door size + 1/4".

OPTIONS

MATERIALS




B Galvanized / bonderized steel
with primer coat. Use where corrosive resistance is required.



S Stainless steel type #304
Extremely resistant to corrosion. With #4 satin polish finish.

ADDITIONAL OPTIONS



G Gasketing
Applied to the doorstops for weather resistance. Also available with UL listed smoke seal.



M Masonry anchors
Attached to the frame to secure the panel when installed in masonry.

HINGE OPTIONS



H Continuous piano hinge
Provides specification compliance when required.



Z Concealed continuous piano hinge
Provides added security while maintaining superior aesthetics.


FLANGES



1" Flange



Drywall bead



Plaster bead

LATCH & LOCK OPTIONS



C Screwdriver operated cam latch
Most common. Appropriate for standard applications.



N Knurled knob cam latch
Unrestricted access – no tool required. Finger operated.



K Knurled knob/key operated latch bolt
Patented ball bearing latch bolt operated by a screw-in type knurled knob or flush key.



L Key operated cam lock
Provides an economical solution for controlled access when locks are required.



M Mortise cylinder lock preparation
Very secure. Matches project hardware. Accepts standard 1.125" mortise cylinder.


POWDER COATING OPTIONS



White

Note: White is the base color, all other colors have additional charges and may require longer lead times.

Colors shown give only an indication of shade. Samples are available upon request.



FP1
ANSI 70
Gray



FP43
Traffic
White

FP44
High Reflectance
White