

TRI-BUILT® CUTTINGEDGE Recessed Access Door

TRI-BUILT® CUTTINGEDGE non-rated Recessed Access Door provides access through openings in vertical or horizontal surfaces. This door is designed to receive 5/8" drywall to match the surrounding surfaces.

- DOOR: 16 gauge cold rolled steel
- FRAME: 16 gauge cold rolled steel
- HINGE: Concealed pivoting rod
- PAN DEPTH: 5/8"
- FINISH: White powder coat paint



TBRWC1212



FLANGE	
A	No flange
W	Drywall bead
P	Plaster casing

LATCH	
C	Screwdriver cam latch
L	Key operated cam latch
M	Mortise lock (1-1/8") prep


STANDARD SIZES (WIDTH & HEIGHT)		
8" x 8"	18" x 18"	24" x 30" *
12" x 12"	20" x 30" *	24" x 36" *
16" x 16"	24" x 24" *	

OPTIONS	
B	Bonderized / galvanized
G	Gasketing
S	T304 Stainless steel


*Rough opening is door size + 1/4".
 * Horizontal applications only.*

OPTIONS

MATERIALS




B Galvanized / bonderized steel
with primer coat. Use where corrosive resistance is required.



S Stainless steel type #304
Extremely resistant to corrosion. With #4 satin polish finish.

ADDITIONAL OPTIONS



G Gasketing
Applied to the doorstops for weather resistance. Also available with UL listed smoke seal.



M Masonry anchors
Attached to the frame to secure the panel when installed in masonry.

HINGE OPTIONS



H Continuous piano hinge
Provides specification compliance when required.



Z Concealed continuous piano hinge
Provides added security while maintaining superior aesthetics.


FLANGES



1" Flange



Drywall bead



Plaster bead

LATCH & LOCK OPTIONS



C Screwdriver operated cam latch
Most common. Appropriate for standard applications.



N Knurled knob cam latch
Unrestricted access – no tool required. Finger operated.



K Knurled knob/key operated latch bolt
Patented ball bearing latch bolt operated by a screw-in type knurled knob or flush key.



L Key operated cam lock
Provides an economical solution for controlled access when locks are required.



M Mortise cylinder lock preparation
Very secure. Matches project hardware. Accepts standard 1.125" mortise cylinder.

POWDER COATING OPTIONS




White

Note: White is the base color, all other colors have additional charges and may require longer lead times.


Colors shown give only an indication of shade. Samples are available upon request.



FP1
ANSI 70
Gray



FP43
Traffic
White



FP44
High Reflectance
White