

TRI-Built® Wet Surface Roof Cement Tube

DESCRIPTION: TRI-BUILT® Wet Surface Roof Cement is a flexible, all-weather cement especially adapted for wet surfaces in adverse or colder weather conditions. TRI-BUILT® Wet Surface Roof Cement is designed and formulated for the professional contractor and is manufactured with select asphalt, solvent and fibers to provide a long lasting, durable patching compound. TRI-BUILT® Wet Surface Roof Cement can be used to patch splits, cracks and seams in bonded gravel, mineral surfaced cap sheet and smooth surface asphalt roofs as well as composition shingle roofs. It will seal areas around chimneys, vent pipes, gravel guards, down spouts or cracks in concrete. TRI-BUILT® Wet Surface Roof Cement is also an excellent utility mastic for use below grade in heavy duty foundation water-proofing and damp-proofing.

PREPARATION: All surfaces must be clean, have proper drainage and be free of surface rust and any other foreign matter. DO NOT HEAT OR THIN.

FOR BEST RESULTS: Apply when surface temperatures are between 40° and 120° F. In colder weather, product should be stored in heated room (65° to 80° F.) at least 24 hours prior to application. Product formulated to be used year round. After a minimum of 45 days cure time, apply TRI-BUILT® Aluminum Roof Coating. This will greatly extend the life of the cement.

APPLICATION: Protective clothing and eyewear should be used during application of these products. Apply with a caulking gun, and if needed, smooth with a putty knife. Work material to an even consistency over and into the area to be repaired. Apply 1/8" to 1/4" thick, two or three inches beyond the problem area. It is highly recommended to reinforce the repair with a strip of reinforcing fabric. Embed fabric into the cement and cover with a second layer of cement. Form a feathered edge with cement where chimneys, vent pipes, and other projections meet the roof line.

PRECAUTIONS: When transporting this product, ensure that plug is tight and tube is secure and upright. Do not allow tube to tumble as this may cause leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 110°F. For exterior use only. Products should be applied in accordance with NRCA guidelines. Do not reuse empty containers. Do not use in drinking water or food systems.

COMPLIANCE: EXCEEDS ASTM D 4586, TYPE 1, ASTM D 6511, ASTM D 3409, ASBESTOS FREE. California products meet Los Angeles County A.P.C.D. (Rule #102).

CLEAN-UP: Clean tools with paint thinner or mineral spirits. **DANGER! HARMFUL OR FATAL IF SWALLOWED. CAUTION! KEEP OUT OF REACH OF CHILDREN.**

For exterior use only. Contains petroleum based products. Keep away from heat, sparks and open flame. Use only with adequate ventilation. Eye, skin and respiratory irritant. Persons with skin or respiratory sensitivity should not use product without sufficient protection. Avoid contact with skin and breathing vapor. If swallowed, do not induce vomiting. Call physician immediately. Seal container when not in use. Do not use in drinking water or food systems.

CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ).

WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. Use proper protection and adequate ventilation, when using product.

VOC/VOS - 250 g/l max. (2.1 lbs./gal.)
PETROLEUM ASPHALT C.A.S.# 8052-42-4
MINERAL SPIRITS C.A.S.# 8052-41-3
CELLULOSE FIBER C.A.S.# 9004-34-6IN
ORGANIC FILLER C.A.S.# 1317-65-3

Product is Asbestos Free. TRI-BUILT® MATERIALS GROUP, LLC warrants to the original end user purchaser ("OEP") that for a one year period, this product will be free of defects in materials under normal use when installed according to label instructions. Call TRI-BUILT® MATERIALS GROUP, LLC for additional conditions and limitations at 800-516-1485.