

TRIBUILT® Quick Dry Asphalt Spray Primer

DESCRIPTION: TRI-BUILT® Quick Dry Asphalt Primer is an aerosol spray primer formulated with a high penetrating solvent and high melt asphalt. It is designed to dry fast and promote superior adhesion of roofing materials. Use to prime newly laid concrete or cement decks, metal flashings, gypsum, masonry thermal insulation, weathered roofing prior to applying built-up roofing, self adhered roofing membranes, roof cements and coatings.

APPLICATION: Shake well before using. Apply to clean, dry surface. Coverage is approximately 35 sq. ft. per can. After using product, clear out spray tip in the following manner: Turn can upside down and point into refuse can. Push spray head for 3 seconds to clear passage of asphalt primer. If valve becomes clogged, remove from can and clean in paint thinner.

CLEAN-UP: Paint thinner.

DANGER!: EXTREMELY FLAMMABLE. DO NOT PUNCTURE, INCINERATE OR BURN CAN, EVEN WHEN EMPTY. CONTENTS UNDER PRESSURE. HARMFUL OR FATAL IF SWALLOWED. EYE, SKIN AND RESPIRATORY IRRITANT. USE WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN.

Contains Petroleum Distillate. Keep away from heat, sparks and open flame. If swallowed DO NOT induce vomiting. Call physician immediately. In case of: Eye contact - flush with plenty of warm water. Skin contact - wash thoroughly with soap and water. Irregular or stopped breathing - administer oxygen, give artificial respiration. Get medical attention (immediately). Avoid prolonged breathing of vapor or spray mist. (NIOSH/MSHA TC 23C or equivalent).MIR 1.20 max.

CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ).

WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. Use proper protection and adequate ventilation, when using product. PETROLEUM ASPHALT C.A.S.# 8052-42-4 MINERAL SPIRITS C.A.S.# 8052-41-3 Product is asbestos free.

TRIBUILT® MATERIALS GROUP, LLC warrants to the original end user purchaser ("OEP") that for a one year period, this product will be free of defects in materials under normal use when installed according to label instructions. Call TRI-BUILT® MATERIALS GROUP, LLC for additional conditions and limitations at 800-516-1485



Promotes Superior Adhesion of Roofing Materials to:

- Weathered Roofing
- Masonry Thermal Insulation
- Metal Flashings & Gypsum
- Concrete & Cement Decks

COMPLIANCE: EXCEEDS ASTM D 41 ASBESTOS FREE