

## TRI-BUILT® Rust Converter and Primer 80450205

TRI-BUILT® Rust Converter can be applied to any iron or steel surface to penetrate rust and turn it into a protective black coating. This protective coating will be resistant to moisture and prevents future rust growth. Just remove any loose rust, then apply it like a primer to rusted surfaces. Greatly reduces time spent wire brushing and sanding. Durable and tough, it can be left as is, but is also compatible with most top coats.

### SUGGESTED USES:

- Vehicles
- Trailers
- Fences
- Railings
- Sheet metal
- Storage tanks
- Furniture
- Tools



### PACKAGING:

UPC Code	811856021350
Cans per case	6
Shipping weight per case	7 lbs.
Container	16 fluid ounce can
Label weight	12 ounces (340 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

### PROPERTIES:

Flammability	“Extremely Flammable”
Flash Point	-4° F
Specific Gravity	0.80
Solids Content	~30%
Mir Value	~1.18, Cannot Exceed 1.20
Storage Temperature	40-100°F
Application Temperature	50-90°F
Durability	Excellent
Abrasion Resistance	Good
Gasoline Resistance	Yes
Heat Resistance	250° F
Resin System	Chain Stopped Alkyd
Shelf Life	Guaranteed For 2 Years

### DRY TIME\*:

To touch	5 minutes
To topcoat	10 minutes

\*At 72° F, 50% humidity,  
 1.5 mil thickness

\*\*Curing/Recoat time is extended with  
 multiple coats and excessively thick  
 coats\*\*

Gloss\*: Flat, <15

\*as measured on a 60° gloss meter