

TRI-BUILT® SYNTHETIC MAX

TRI-BUILT® Synthetic Max is a synthetic roof-deck protection designed and manufactured to replace asphalt saturated 30# felt in sloped roof system construction where toughness and longer exposures may be required.

- Best substitute for 30# organic felt
- Use under Asphalt Shingles, Stone Coated Metal Shingles, Synthetic Slate, Wood Shakes, Terra Cotta Tile, Concrete Tile, Slate, Sloped Standing Seam Metal Roofing
- 14 mils thick
- 6 month UV exposure
- Rolls out flat and does not wrinkle
- 33% more coverage per pass across the roof (vs. 36" wide rolls)
- Great walkability due to Anti-Slip engineered back
- Designed to perform in virtually all steep slope roof covering systems and in extreme weather conditions
- Water resistive coating which doesn't absorb water, won't rot and is inert to mold growth
- Florida Building Code approved FL21553
- Life Time Warranty



Specifications	TRI-BUILT Synthetic Max	30# Conventional Felt
Composite Material	Woven Polypropylene Fabric	Asphalt
Width Per Roll	48"	36"
Length Per Roll	250 ft.	72 ft.
Weight Per Roll	35 lbs.	32 lbs. to 60 lbs.
Roll Size	10 sq.	2 sq.
Rolls Per Pallet	36	30
Permeability	.06 perms	1.75 perms
Water Transmission	PASS – ASTM4869	PASS - ASTM4869
Tear Strength	MD 62 lbs. / CD 62 lbs.	MD 4 lbs. / CD 2 lbs.
Tensile Strength	MD 93 lbs. / CD 93 lbs.	MD 70 lbs. / 38 lbs.
Elongation	MD 20% / CD 20%	MD 2% / CD 2%
UV-Resistant	Yes - Up to 6 Months	NO
Class A Fire Rated	Yes	NO
Pre-Printed Nailing Pattern	Yes	NO
Temperature Range	240F	N/A
Warranty	Life Time	NONE