

TRI-BUILT® CUTTINGEDGE Ceiling Tile Paint 80450390 New White

A special water based formulation for touching up stains that appear on both textured and acoustical ceiling tiles. Must be used in an upright position and is activated by tipping sprayhead to the side.

SUGGESTED USES:

- All fiber type ceiling tiles
- Air conditioning vents

BENEFITS:

- Fast drying
- Maintains acoustic properties
- Easy over-head application
- Matches color of tile
- Will not warp or sag tiles
- Environmentally Friendly
- VOC Compliant



PACKAGING:

UPC Code	811856021367
Cans per case	6
Shipping weight per case	9 lbs.
Container	20 fluid ounce can
Label weight	16 ounces (454 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

PROPERTIES:

Flammability	“Flammable”
Flash Point	-4°F
Specific Gravity	0.83
Solids Content	~22%
Voc Content	~57%, Cannot Exceed 60%
Mir Value	~1.13, Cannot Exceed 1.20
Haps Content	~16%
Storage Temperature	40-100°F
Application Temperature	50-90°F
Durability	Good
Abrasion Resistance	Fair
Heat Resistance	250° F
Resin System	V.T. Alkyd
Shelf Life	Guaranteed For 2 Years
Food Contact Rating	No

DRY TIME*:

To Touch 15 Minutes

*At 72° F, 50% Humidity,
 1.5 Mil Thickness

**Curing/recoat time is extended with
 Multiple coats and excessively thick coats**

Gloss*: Flat, <15

*As measured on a 60° Gloss Meter